

newly introduced CertiFlux LED Panel Gen2(backlit) brings the next level of cost-effectiveness using backlit technology and comes in combination with different panel drivers as system offer.



Product information

Product Description	Product code	Light output lm	Panel efficacy lm/W	Color Temperature K	Color Rendering Ra	Color Consistency SDCM	B50/L70 at 7c Life hrs
	12NC						
CertiFlux LED BL Panel 6060 830 MD2	929002847506	3100	104	3000	80	6	30000
CertiFlux LED BL Panel 6060 840 MD2	929002847606	3350	112	4000	80	6	30000
CertiFlux LED BL Panel 6060 865 MD2	929002847706	3350	112	6500	80	6	30000
CertiFlux LED BL Panel 6060 sCCT MD2	929002847806	*3100@4000K 3100@6500K	*114@4000K 114@6500K	*4000 126@5000K 6500	80	6	30000
CertiFlux LED BL Panel 6060L 830 MD2	929002847906	3100	104	3000	80	6	30000
CertiFlux LED BL Panel 6060L 840 MD2	929002848006	3350	112	4000	80	6	30000
CertiFlux LED BL Panel 6060L 865 MD2	929002848106	3350	112	6500	80	6	30000
CertiFlux LED BL Panel 30120 830 MD2	929002848206	3100	104	3000	80	6	30000
CertiFlux LED BL Panel 30120 840 MD2	929002848306	3350	112	4000	80	6	30000
CertiFlux LED BL Panel 30120 865 MD2	929002848406	3350	112	6500	80	6	30000
CertiFlux LED BL Panel 60120 830 MD2	929002848506	5800	104	3000	80	6	30000
CertiFlux LED BL Panel 60120 840 MD2	929002848606	6200	111	4000	80	6	30000
CertiFlux LED BL Panel 60120 865 MD2	929002848706	6200	111	6500	80	6	30000

Accessories

Product Description	Product code
	12NC
LED BL Panel safety cable accessory set	929002848806

* Module Light output and efficacy is calculated @ typical. Measurement precision for flux +/-5%, Measurement precision for efficacy +/- 6%. For more detailed specifications (including lifetime) please approach local sales team.

Compatible LED Drivers

CertaDrive LED drivers are designed to fulfill the market need for essential lighting. The CertaDrive LED drivers offer basic specifications such as specific current and voltage settings, optimized for operating CertiFlux LED modules. For a detailed overview of all CertaDrive LED linear drivers see page 97-104.

Product Description	12NC	60x60	30x120	60x120	60x60 sCCT
CertaDrive 34W 0.7/0.8A 42V 230V I	929002804780	√	√	√	√
CertaDrive 44W 0.9/1.05A 42V 230V I	929002804880	√	√	√	√
Xtaram 34W/m 0.8A 42V 5C 230V	929002105206	√	√	√	√
Xtaram 36W/m 0.85A 42V 5C 230V	929002139306	√	√	√	√
Xtaram 38W/m 0.9A 42V 5C 230V	92900213406	√	√	√	√
Xtaram 34W 0.8A 42V 1-10V 230V I	929001486380	√	√	√	√
Xtaram 38W 0.9A 42V 1-10V 230V I	929001486480	√	√	√	√
Xtaram 44W 1.05A 42V 1-10V 230V I	929001486580	√	√	√	√
Xtaram 64W 1.5A 1.6A 40V I 230V	929001423580			√	
Xtaram 75W 0.7-2A 54V TD 230V	929001503706			√	

